



INBOARD INSERTION BLOCKING (IIB) REVERSE PRESSURE TEST PLUG 3/4" TO 4"* SPECIFICATIONS & RATINGS



Nominal Pipe Size (in)	Schedule	Part Number	Tool Diameter (in)	Rec. ID Range* (in)	Nominal Pipe ID Clearance (in)	Approx. Tool Weight (lbs)	Tool Length (in)	Torque Range (ft-lbs)		Compr Hex Nut Socket Size (in)	Backup Wrench Size (in)	Back Pressure Vent Thread	Test Pressure Rating (PSI)*
								Norm	Max.				
3/4	40,STD,40S	GSST-I-R-0075-040	0.79	0.80 - 0.87	0.035	0.6	8.69	2.9	4.5	1/2	1/4 Open End	1/4 MNPT	10000
	80,XS,80S	GSST-I-R-0075-080	0.71	0.72 - 0.79	0.035	0.6	8.69	2.2	3.5	1/2	1/4 Open End	1/4 MNPT	10000
1	10	GSST-I-R-0100-010	1.04	1.06 - 1.16	0.055	0.8	9.19	6.3	9.7	9/16	1/4 Open End	1/16 MNPT	10000
	40,STD,40S	GSST-I-R-0100-040	0.99	1.02 - 1.11	0.055	0.8	9.19	5.6	8.7	9/16	1/4 Open End	1/16 MNPT	10000
	80,XS,80S	GSST-I-R-0100-080	0.90	0.92 - 1.02	0.055	0.8	9.19	4.5	6.9	9/16	1/4 Open End	1/16 MNPT	10000
	160	GSST-I-R-0100-160	0.78	0.79 - 0.85	0.035	0.6	8.69	2.8	4.4	1/2	1/4 Open End	1/4 MNPT	10000
1-1/4	10	GSST-I-R-0125-010	1.38	1.39 - 1.54	0.068	1.9	12.19	15	23	3/4	3/8 Open End	1/8 MNPT	10000
	40,STD,40S	GSST-I-R-0125-040	1.31	1.33 - 1.48	0.068	1.9	12.19	13	20	3/4	3/8 Open End	1/8 MNPT	10000
	80,XS,80S	GSST-I-R-0125-080	1.21	1.23 - 1.38	0.065	1.8	12.19	11	17	3/4	3/8 Open End	1/8 MNPT	10000
	160	GSST-I-R-0125-160	1.11	1.12 - 1.22	0.055	0.9	9.19	7.2	11	9/16	1/4 Open End	1/16 MNPT	10000
	XX	GSST-I-R-0125-XXH	0.86	0.87 - 0.94	0.045	0.6	8.69	3.5	5.5	1/2	1/4 Open End	1/4 MNPT	10000
1-1/2	10	GSST-I-R-0150-010	1.60	1.64 - 1.80	0.085	2.4	12.63	24	37	15/16	7/16 Open End	1/4 MNPT	10000
	40,STD,40S	GSST-I-R-0150-040	1.53	1.56 - 1.73	0.085	2.3	12.63	21	33	15/16	7/16 Open End	1/4 MNPT	10000
	80,XS,80S	GSST-I-R-0150-080	1.42	1.45 - 1.62	0.085	2.1	12.63	18	28	15/16	7/16 Open End	1/4 MNPT	10000
	160	GSST-I-R-0150-160	1.27	1.30 - 1.44	0.068	1.8	12.19	12	19	3/4	3/8 Open End	1/8 MNPT	10000
	XX	GSST-I-R-0150-XXH	1.05	1.08 - 1.16	0.055	0.8	9.19	6.3	9.8	9/16	1/4 Open End	1/16 MNPT	10000
2	10	GSST-I-R-0200-010	2.03	2.05 - 2.28	0.130	4.0	13.63	47	75	1-1/8	9/16 Open End	3/8 MNPT	10000
	40,STD,40S	GSST-I-R-0200-040	1.94	1.97 - 2.19	0.130	3.8	13.63	42	65	1-1/8	9/16 Open End	3/8 MNPT	10000
	80,XS,80S	GSST-I-R-0200-080	1.81	1.84 - 2.06	0.130	3.5	13.63	36	55	1-1/8	9/16 Open End	3/8 MNPT	10000
	160	GSST-I-R-0200-160	1.60	1.64 - 1.80	0.085	2.4	12.63	24	37	15/16	7/16 Open End	1/4 MNPT	10000
	XX	GSST-I-R-0200-XXH	1.42	1.45 - 1.62	0.085	2.2	12.63	18	28	15/16	7/16 Open End	1/4 MNPT	10000
2-1/2	10	GSST-I-R-0250-010	2.51	2.57 - 2.77	0.125	7.2	15.38	85	135	1-5/16	9/16 Open End	3/8 MNPT	8000
	40,STD,40S	GSST-I-R-0250-040	2.34	2.38 - 2.61	0.125	6.6	15.38	75	115	1-5/16	9/16 Open End	3/8 MNPT	8000
	80,XS,80S	GSST-I-R-0250-080	2.20	2.24 - 2.46	0.125	6.2	15.38	65	100	1-5/16	9/16 Open End	3/8 MNPT	8000
	160	GSST-I-R-0250-160	2.00	2.06 - 2.25	0.125	3.9	13.63	46	70	1-1/8	9/16 Open End	3/8 MNPT	10000
	XX	GSST-I-R-0250-XXH	1.69	1.74 - 1.89	0.085	2.5	12.63	27	42	15/16	7/16 Open End	1/4 MNPT	10000
3	10	GSST-I-R-0300-010	3.07	3.10 - 3.44	0.193	9.1	15.38	150	230	1-1/2	3/4 Box End	1/4 FNPT	8000
	40,STD,40S	GSST-I-R-0300-040	2.88	2.92 - 3.25	0.193	9.7	15.38	130	200	1-1/2	3/4 Box End	1/4 FNPT	8000
	80,XS,80S	GSST-I-R-0300-080	2.71	2.75 - 3.09	0.190	9.0	15.38	110	175	1-1/2	3/4 Box End	1/4 FNPT	8000
	160	GSST-I-R-0300-160	2.50	2.56 - 2.76	0.125	6.1	15.38	85	130	1-5/16	9/16 Open End	3/8 MNPT	8000
	XX	GSST-I-R-0300-XXH	2.18	2.24 - 2.42	0.125	6.1	13.63	55	85	1-1/8	9/16 Open End	3/8 MNPT	8000
3-1/2	10	GSST-I-R-0350-010	3.56	3.61 - 3.96	0.204	11.1	15.38	225	350	1-11/16	7/8 Box End	3/8 FNPT	6000
	40,STD,40S	GSST-I-R-0350-040	3.34	3.39 - 3.75	0.204	13.4	15.38	195	305	1-11/16	7/8 Box End	3/8 FNPT	6000
	80,XS,80S	GSST-I-R-0350-080	3.16	3.21 - 3.56	0.208	12.3	15.38	175	270	1-11/16	7/8 Box End	3/8 FNPT	6000
	XX	GSST-I-R-0350-XXH	2.60	2.66 - 2.86	0.125	7.5	15.38	95	145	1-5/16	9/16 Open End	3/8 MNPT	8000
4	120	GSST-I-R-0400-120	3.42	3.52 - 3.83	0.205	10.5	15.38	205	320	1-11/16	7/8 Box End	3/8 FNPT	6000
	160	GSST-I-R-0400-160	3.23	3.33 - 3.64	0.205	9.7	15.38	185	285	1-11/16	7/8 Box End	3/8 FNPT	6000
	XX	GSST-I-R-0400-XXH	2.96	2.99 - 3.34	0.193	8.6	15.38	135	215	1-1/2	3/4 Box End	1/4 FNPT	8000

* NPS 6-36 TOOL OD MUST BE WITHIN 1/8" CONCENTRICITY TO THE PIPE ID.

* Larger sizes and custom configurations available upon request. Smaller sizes release date pending. ** NOTE: IIB Reverse Pressure Plugs are not rated for Back Pressure.

• **WARNING ABOUT TESTING AND SYSTEM LIMITS:** Flanges used with the IIB may be rated to less than the pressure rating of plug.

• **NEVER EXCEED THE MAXIMUM RATED PRESSURE OF THE LOWEST RATED COMPONENT IN THE SYSTEM.**

• **DATA IS SUBJECT TO CHANGE.** Consult manufacturer to verify that this document is the latest release.



For more information on USA Industries' products, contact us at (713) 941-3797 or go to www.USAIndustries.com



INBOARD INSERTION BLOCKING (IIB) REVERSE PRESSURE TEST PLUG 4" TO 14"* SPECIFICATIONS & RATINGS



Nominal Pipe Size (in)	Schedule	Part Number	Tool Diameter (in)	Rec. ID Range* (in)	Nominal Pipe ID Clearance (in)	Approx. Tool Weight (lbs)	Tool Length (in)	Torque Range (ft-lbs)		Comp. Hex Nut Socket Size (in)	Back Pressure Vent Thread	Test Pressure Rating (PSI)*
								Norm	Max.			
4	10,10S	GS-I-R-0400-010	4.04	4.10 - 4.54	0.22	21	13.94	120	250	1-5/16	1/4 FNPT	4875
	40,STD,40S	GS-I-R-0400-040	3.81	3.87 - 4.31	0.22	19	13.94	120	250	1-5/16	1/4 FNPT	5450
	80,XS,80S	GS-I-R-0400-080	3.61	3.67 - 4.11	0.22	17	13.94	120	250	1-5/16	1/4 FNPT	6050
6	10,10S	GS-I-R-0600-010	5.98	6.04 - 6.42	0.375	34	16.42	85	130	1-1/16	1/4 MNPT	850
	40,STD,40S	GS-I-R-0600-040	5.69	5.75 - 6.13	0.375	32	16.42	75	110	1-1/16	1/4 MNPT	2370
	80,XS,80S	GS-I-R-0600-080	5.39	5.45 - 5.82	0.375	29	16.42	60	95	1-1/16	1/4 MNPT	4000
	120	GS-I-R-0600-120	5.13	5.19 - 5.56	0.375	27	16.42	55	80	1-1/16	1/4 MNPT	3900
	160	GS-I-R-0600-160	4.81	4.87 - 5.25	0.375	25	16.42	40	60	3/4	1/4 MNPT	3850
	XX	GS-I-R-0600-XXH	4.52	4.58 - 4.96	0.375	23	16.42	35	55	3/4	1/4 MNPT	3700
8	10,10S	GS-I-R-0800-010	7.95	8.02 - 8.40	0.375	61	16.28	120	150	1-1/4	1/2 MNPT	575
	20	GS-I-R-0800-020	7.75	7.81 - 8.20	0.375	59	16.28	120	150	1-1/4	1/2 MNPT	1125
	30	GS-I-R-0800-030	7.70	7.76 - 8.15	0.375	58	16.28	120	150	1-1/4	1/2 MNPT	1300
	40,STD,40S	GS-I-R-0800-040	7.61	7.67 - 8.05	0.375	56	16.28	120	150	1-1/4	1/2 MNPT	1575
	60	GS-I-R-0800-060	7.44	7.50 - 7.89	0.375	55	16.28	120	150	1-1/4	1/2 MNPT	2175
	80,XS,80S	GS-I-R-0800-080	7.25	7.31 - 7.70	0.375	53	16.28	120	150	1-1/4	1/2 MNPT	3250
	100	GS-I-R-0800-100	7.06	7.12 - 7.51	0.375	50	16.28	100	150	1-1/4	1/2 MNPT	3860
	120	GS-I-R-0800-120	6.81	6.87 - 7.26	0.375	48	16.28	100	150	1-1/4	1/2 MNPT	3725
	140	GS-I-R-0800-140	6.63	6.69 - 7.07	0.375	46	16.28	90	150	1-1/16	1/4 MNPT	3925
	160	GS-I-R-0800-160	6.44	6.50 - 6.88	0.375	44	16.28	90	150	1-1/16	1/4 MNPT	3825
XX	GS-I-R-0800-XXH	6.50	6.56 - 6.94	0.375	44	16.28	90	150	1-1/16	1/4 MNPT	3750	
10	10,10S	GSST-I-R-1000-010	10.05	10.11 - 10.85	0.375	75	16.02	120	270	1-1/4	3/4 MNPT	4200
	20	GSST-I-R-1000-020	9.88	9.94 - 10.68	0.375	72	16.02	120	270	1-1/4	3/4 MNPT	4500
	30	GSST-I-R-1000-030	9.76	9.82 - 10.56	0.375	71	16.02	120	270	1-1/4	3/4 MNPT	4800
	40,4STD,40s	GSST-I-R-1000-040	9.65	9.71 - 10.45	0.375	69	16.02	120	270	1-1/4	3/4 MNPT	5000
	60,XS,80S	GSST-I-R-1000-08S	9.38	9.44 - 10.18	0.375	66	16.02	120	270	1-1/4	3/4 MNPT	5975
	80	GSST-I-R-1000-080	9.19	9.25 - 9.99	0.375	63	16.02	120	200	1-1/4	3/4 MNPT	5700
	100	GSST-I-R-1000-100	8.94	9.00 - 9.74	0.375	58	16.02	120	195	1-1/4	3/8 MNPT	6000
	120	GSST-I-R-1000-120	8.69	8.75 - 9.49	0.375	56	16.02	120	185	1-1/4	3/8 MNPT	5775
140,XX	GSST-I-R-1000-140	8.38	8.44 - 9.18	0.375	54	16.02	120	180	1-1/4	3/8 MNPT	5575	
160	GSST-I-R-1000-160	8.13	8.19 - 8.93	0.375	53	16.02	120	175	1-1/4	3/8 MNPT	5925	
12	10,10S	GSST-I-R-1200-010	12.02	12.08 - 12.82	0.375	140	16.02	120	180	1-1/4	3/4 MNPT	5500
	20	GSST-I-R-1200-020	11.88	11.94 - 12.68	0.375	137	16.02	120	175	1-1/4	3/4 MNPT	5625
	30	GSST-I-R-1200-030	11.72	11.78 - 12.52	0.375	133	16.02	120	175	1-1/4	3/4 MNPT	5475
	STD,40S	GSST-I-R-1200-04S	11.63	11.69 - 12.43	0.375	131	16.02	120	250	1-1/4	3/4 MNPT	4550
	40	GSST-I-R-1200-040	11.56	11.63 - 12.36	0.375	129	16.02	120	245	1-1/4	3/4 MNPT	4700
	XS,80S	GSST-I-R-1200-08S	11.38	11.44 - 12.18	0.375	126	16.02	120	225	1-1/4	3/4 MNPT	5175
	60	GSST-I-R-1200-060	11.25	11.31 - 12.05	0.375	97	16.02	120	165	1-1/4	3/4 MNPT	5575
	80	GSST-I-R-1200-080	11.00	11.06 - 11.80	0.375	93	16.02	120	160	1-1/4	3/4 MNPT	5825
	100	GSST-I-R-1200-100	10.69	10.75 - 11.49	0.375	89	16.02	120	235	1-1/4	3/4 MNPT	5775
	120,XX	GSST-I-R-1200-120	10.38	10.44 - 11.18	0.375	87	16.02	120	230	1-1/4	3/4 MNPT	5700
140	GSST-I-R-1200-140	10.13	10.19 - 10.93	0.375	85	16.02	120	220	1-1/4	3/4 MNPT	5550	
160	GSST-I-R-1200-160	9.75	9.81 - 10.55	0.375	81	16.02	120	215	1-1/4	3/4 MNPT	5975	
14	10S	GSST-I-R-1400-01S	13.25	13.31 - 14.05	0.375	182	17.75	120	200	1-1/4	1 MNPT	6250
	10	GSST-I-R-1400-010	13.13	13.19 - 13.93	0.375	179	17.75	120	195	1-1/4	1 MNPT	6350
	20	GSST-I-R-1400-020	13.00	13.06 - 13.80	0.375	176	17.75	120	195	1-1/4	1 MNPT	6475
	30,STD,40S	GSST-I-R-1400-04S	12.88	12.94 - 13.68	0.375	170	17.75	120	205	1-1/4	1 MNPT	6175
	40	GSST-I-R-1400-040	12.75	12.81 - 13.55	0.375	169	17.75	120	195	1-1/4	1 MNPT	6275
	XS,80S	GSST-I-R-1400-08S	12.63	12.69 - 13.43	0.375	166	17.75	120	180	1-1/4	1 MNPT	6400
	60	GSST-I-R-1400-060	12.44	12.50 - 13.24	0.375	148	16.02	120	185	1-1/4	3/4 MNPT	5425
	80	GSST-I-R-1400-080	12.13	12.19 - 12.93	0.375	142	16.02	120	180	1-1/4	3/4 MNPT	5400
	100	GSST-I-R-1400-100	11.75	11.81 - 12.55	0.375	134	16.02	120	175	1-1/4	3/4 MNPT	5425
	120	GSST-I-R-1400-120	11.44	11.50 - 12.24	0.375	130	16.02	120	170	1-1/4	3/4 MNPT	5725
140	GSST-I-R-1400-140	11.13	11.19 - 11.93	0.375	124	16.02	120	165	1-1/4	3/4 MNPT	5700	
160	GSST-I-R-1400-160	10.81	10.88 - 11.61	0.375	118	16.02	120	160	1-1/4	3/4 MNPT	5650	

* NPS 6-36 TOOL OD MUST BE WITHIN 1/8" CONCENTRICITY TO THE PIPE ID.

* Larger sizes and custom configurations available upon request. Smaller sizes release date pending. ** NOTE: IIB Reverse Pressure Plugs are not rated for Back Pressure.

• **WARNING ABOUT TESTING AND SYSTEM LIMITS:** Flanges used with the IIB may be rated to less than the pressure rating of plug.

• **NEVER EXCEED THE MAXIMUM RATED PRESSURE OF THE LOWEST RATED COMPONENT IN THE SYSTEM.**

• **DATA IS SUBJECT TO CHANGE.** Consult manufacturer to verify that this document is the latest release.



For more information on USA Industries' products, contact us at (713) 941-3797 or go to www.USAIndustries.com



INBOARD INSERTION BLOCKING (IIB) REVERSE PRESSURE TEST PLUG 16" TO 24"* SPECIFICATIONS & RATINGS



Nominal Pipe Size (in)	Schedule	Part Number	Tool Diameter (in)	Rec. ID Range* (in)	Nominal Pipe ID Clearance (in)	Approx. Tool Weight (lbs)	Tool Length (in)	Torque Range (ft-lbs)		Comp. Hex Nut Socket Size (in)	Back Pressure Vent Thread	Test Pressure Rating (PSI)*
								Norm	Max.			
16	10S	GSST-I-R-1600-01S	15.25	15.31 - 16.05	0.375	252	18.06	120	310	1-5/8	1 MNPT	6000
	10	GSST-I-R-1600-010	15.13	15.19 - 15.93	0.375	249	18.06	120	305	1-5/8	1 MNPT	6100
	20	GSST-I-R-1600-020	15.00	15.06 - 15.80	0.375	246	18.06	120	300	1-5/8	1 MNPT	6200
	30,STD,40S	GSST-I-R-1600-04S	14.88	14.94 - 15.68	0.375	240	18.07	120	320	1-5/8	1 MNPT	5700
	40,XS,80S	GSST-I-R-1600-08S	14.63	14.69 - 15.43	0.375	234	18.07	120	280	1-5/8	1 MNPT	6175
	60	GSST-I-R-1600-060	14.31	14.38 - 15.11	0.375	225	18.07	120	285	1-5/8	1 MNPT	6075
	80	GSST-I-R-1600-080	13.94	14.00 - 14.74	0.375	190	16.33	120	270	1-5/8	3/4 MNPT	4975
	100	GSST-I-R-1600-100	13.56	13.63 - 14.36	0.375	191	16.33	120	270	1-5/8	3/4 MNPT	5050
	120	GSST-I-R-1600-120	13.19	13.25 - 13.99	0.375	183	16.33	120	265	1-5/8	3/4 MNPT	5350
	140	GSST-I-R-1600-140	12.75	12.81 - 13.55	0.375	154	16.02	120	190	1-1/4	3/4 MNPT	5175
160	GSST-I-R-1600-160	12.44	12.50 - 13.24	0.375	150	16.02	120	185	1-1/4	3/4 MNPT	5425	
18	10S	GSST-I-R-1800-01S	17.25	17.31 - 18.05	0.375	351	19.08	120	430	1-5/8	1 MNPT	4175
	10	GSST-I-R-1800-010	17.13	17.19 - 17.93	0.375	347	19.08	120	430	1-5/8	1 MNPT	4200
	20	GSST-I-R-1800-020	17.00	17.06 - 17.80	0.375	344	19.08	120	425	1-5/8	1 MNPT	4250
	STD,40S	GSST-I-R-1800-04S	16.88	16.94 - 17.68	0.375	335	19.33	120	485	1-5/8	1 MNPT	3550
	30	GSST-I-R-1800-030	16.75	16.81 - 17.55	0.375	331	19.33	120	465	1-5/8	1 MNPT	3750
	XS,80S	GSST-I-R-1800-08S	16.63	16.69 - 17.43	0.375	328	19.33	120	440	1-5/8	1 MNPT	4000
	40	GSST-I-R-1800-040	16.50	16.56 - 17.30	0.375	288	18.07	120	410	1-5/8	1 MNPT	4350
	60	GSST-I-R-1800-060	16.13	16.19 - 16.93	0.375	267	18.07	120	400	1-5/8	1 MNPT	4450
	80	GSST-I-R-1800-080	15.75	15.81 - 16.55	0.375	266	18.07	120	390	1-5/8	1 MNPT	4525
	100	GSST-I-R-1800-100	15.31	15.38 - 16.11	0.375	234	17.10	120	380	1-5/8	1 MNPT	4650
	120	GSST-I-R-1800-120	14.88	14.94 - 15.68	0.375	215	17.22	120	370	1-5/8	1 MNPT	4900
	140	GSST-I-R-1800-140	14.50	14.56 - 15.30	0.375	211	17.35	120	360	1-5/8	1 MNPT	5075
160	GSST-I-R-1800-160	14.06	14.13 - 14.86	0.375	201	17.47	120	345	1-5/8	1 MNPT	5150	
20	10S	GSST-I-R-2000-01S	19.19	19.25 - 19.99	0.375	438	19.56	120	365	1-5/8	1-1/2 MNPT	5000
	10	GSST-I-R-2000-010	19.13	19.19 - 19.93	0.375	436	19.56	120	360	1-5/8	1-1/2 MNPT	5025
	20,STD,40S	GSST-I-R-2000-04S	18.88	18.94 - 19.68	0.375	427	19.56	120	415	1-5/8	1-1/2 MNPT	4275
	30,XS,80S	GSST-I-R-2000-08S	18.63	18.69 - 19.43	0.375	415	19.56	120	375	1-5/8	1-1/2 MNPT	4500
	40	GSST-I-R-2000-040	18.44	18.50 - 19.24	0.375	409	19.56	120	350	1-5/8	1-1/2 MNPT	5250
	60	GSST-I-R-2000-060	18.00	18.06 - 18.80	0.375	391	19.56	120	340	1-5/8	1-1/2 MNPT	5375
	80	GSST-I-R-2000-080	17.56	17.63 - 18.36	0.375	336	18.30	120	330	1-5/8	1-1/2 MNPT	5475
	100	GSST-I-R-2000-100	17.06	17.13 - 17.86	0.375	320	18.30	120	320	1-5/8	1-1/2 MNPT	5625
	120	GSST-I-R-2000-120	16.63	16.69 - 17.43	0.375	305	18.30	120	310	1-5/8	1-1/2 MNPT	5750
	140	GSST-I-R-2000-140	16.13	16.19 - 16.93	0.375	279	18.42	120	400	1-5/8	1-1/2 MNPT	5950
160	GSST-I-R-2000-160	15.69	15.75 - 16.49	0.375	265	18.42	120	390	1-5/8	1-1/2 MNPT	5975	
24	10,10S	GSST-I-R-2400-01S	23.13	23.19 - 23.93	0.375	653	20.36	120	465	1-5/8	1-1/2 MNPT	3700
	20,STD,40S	GSST-I-R-2400-04S	22.88	22.94 - 23.68	0.375	635	20.36	120	510	1-5/8	1-1/2 MNPT	3600
	XS,80S	GSST-I-R-2400-08S	22.63	22.69 - 23.43	0.375	625	20.36	120	465	1-5/8	1-1/2 MNPT	3675
	30	GSST-I-R-2400-030	22.50	22.56 - 23.30	0.375	626	20.36	120	450	1-5/8	1-1/2 MNPT	3725
	40	GSST-I-R-2400-040	22.25	22.31 - 23.05	0.375	608	20.36	120	445	1-5/8	1-1/2 MNPT	3650
	60	GSST-I-R-2400-060	21.69	21.75 - 22.49	0.375	585	20.36	120	435	1-5/8	1-1/2 MNPT	3825
	80	GSST-I-R-2400-080	21.19	21.25 - 21.99	0.375	518	19.56	120	425	1-5/8	1-1/2 MNPT	4375
	100	GSST-I-R-2400-100	20.56	20.63 - 21.36	0.375	492	19.56	120	410	1-5/8	1-1/2 MNPT	4500
	120	GSST-I-R-2400-120	20.00	20.06 - 20.80	0.375	468	19.69	120	395	1-5/8	1-1/2 MNPT	5250
	140	GSST-I-R-2400-140	19.50	19.56 - 20.30	0.375	450	19.81	120	385	1-5/8	1-1/2 MNPT	5100
160	GSST-I-R-2400-160	18.94	19.00 - 19.74	0.375	428	19.94	120	375	1-5/8	1-1/2 MNPT	5125	

• NPS 6-36 TOOL OD MUST BE WITHIN 1/8" CONCENTRICITY TO THE PIPE ID.

* Larger sizes and custom configurations available upon request. Smaller sizes release date pending. ** NOTE: IIB Reverse Pressure Plugs are not rated for Back Pressure.

• **WARNING ABOUT TESTING AND SYSTEM LIMITS:** Flanges used with the IIB may be rated to less than the pressure rating of plug.

• **NEVER EXCEED THE MAXIMUM RATED PRESSURE OF THE LOWEST RATED COMPONENT IN THE SYSTEM.**

• **DATA IS SUBJECT TO CHANGE.** Consult manufacturer to verify that this document is the latest release.



For more information on USA Industries' products, contact us at (713) 941-3797 or go to www.USAIndustries.com